



PRODUCT DATA SHEET

2T Machines Smokeless Engine Oil

TWO STROKE

SMOKELESS LUBRICANT *New Improved Formula with Friction Modifier*

Product Description

TOYO-G 2T Machines is a Long Lasting Performance 2-strokes engine oil formulated from high quality paraffinic base stocks and special additives package to ensure optimum lubricating performance for most outdoor gardening equipment.

It is specially designed for both injection and premix application up to a fuel ratio at 50:1. With anti-wear, anti corrosion and anti-foam capabilities.

Product Specifications & Application

Outdoor Power Equipment such as Lawn Mover, Generator Set, Trimmer or Weed eaters & Brushcutters.

Specification meets or exceed JASO FC / ISO-L-EGC / API TC

Ratio
50:1

Jaso
FC

Benefits

- ✓ Preserve Power Output and Enhance Fuel Consumption Efficiency and Economy.
- ✓ Excellent Start-up Protection and Rapid Circulation.
- ✓ Designed to Protect Against High Friction and High Shear.
- ✓ Protection against thermal and machine breakdown.
- ✓ Assist engine cleanliness and virtually smokeless exhaust.
- ✓ Minimizing spark plug fouling to ensure that reliable starting.
- ✓ Carbonless which can be the sign of environment friendly.

Typical Specifications

	Grade	Test Method	Spec
	API Gravity	ASTM D-1298	0.894
	Kinematic Viscosity at		
	40°C cSt	ASTM D-445	52
	100°C cSt	ASTM D-445	7.3
	Viscosity Index	ASTM D-2270	99
	Flash Point min °C	ASTM D-92	>200
	Pour Point °C	ASTM D-97	-13
	Zinc % wt	ASTM D-4951	0.001

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.





PRODUCT DATA SHEET

2T Machines Smokeless Engine Oil

TWO STROKE

Other Information

Safety Data Sheet

Safety data sheet can be requested via website www.toyointernational.com or you may also can get them from your local agent / supplier.

SDS Number: LP06-02

Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Suggested temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled.

Stirring is recommended in order to prevent ingredients from separating.

Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 5 years or 60 months

Condition of the product must in the unopened original container

Available Packing Sizes

Bottle	1 liter
Pail	18 liter
Drum	209 liter

Part Number

8696L-0196
8696L-0207
8696L-0212

Packing Type

12 pcs per box

Updated 15.09.2022

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

TOYO-G