



PRODUCT DATA SHEET

ATF MULTI-VEHICLE LOW VISCOSITY

FULLY SYNTHETIC

DESCRIPTION

TOYO-G ATF MULTI-VEHICLE LV is a Fully Synthetic Multi-Vehicle Automatic Transmission Fluid which formulated for broad market coverage including Asian, European and North American vehicles especially for today's commercial or passenger vehicles running with higher mileages. It's containing an uncompromised wear protection so as to extend longer oil drain interval comparing with other automatic transmission fluid.

With MV technology, it can be used in 6 speed, 7 speed or even 8 speed automatic transmission.

TOYO-G ATF MULTI-VEHICLE LV provides better wear and seals protection for older vehicles and stronger durability for the increasing of Asian and Europe vehicle models.

Recommended Oil Drain Interval (with good condition transmission)

> 100,000 KM

Benefits

- ✓ Reduce logistical complexity
- ✓ Carry less ATF inventory
- ✓ Lower viscosity grade for fuel economy, wear and seals protection
- ✓ Reduce Risks since it is less likely to use an incorrect fluid
- ✓ Increase product availability by stocking one ATF for use in multiple vehicles
- ✓ It provides world class frictional and anti-shudder durability (ASD) characteristics
- ✓ Meets the requirement of Jaso 1-A and Jaso 1-A LV

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	ATF MVL
API GRAVITY AT 15°C	ASTM D-1298	0.820
VISCOSITY INDEX	ASTM D-2270	157
POUR POINT °C	ASTM D-97	-44
FLASH POINT °C	ASTM D-92	>200
KINEMATIC VISCOSITY		
40 °C mm ² /s (cSt)	ASTM D-445	30.0
100 °C mm ² /s (cSt)	ASTM D-445	6.10
BROOKFIELD VIS AR -40°C, cP	ASTM D-2983	10,600
COLOUR	ASTM D-1500	Gold / Original

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

TOYO-G



PRODUCT DATA SHEET

ATF MULTI-VEHICLE LOW VISCOSITY

FULLY SYNTHETIC

Other Information

Product Specifications & Performance (Suitable for use)

AISIN WARNER AW-1	LAND ROVER P/N TYK500050, LR0022460
ATF M1375.4	MERCEDES BENZ 236.12, 236.14, 236.15, 236.41
AUDI G 055 005, 055 162	MINI 83 22 0 142 516, 83 22 2 152 426
BMW 83 22 0 142 516, 83 22 2 152 426	MINI 83 22 0 142 516, 83 22 2 152 426
HONDA / ACURA DW-1	LAND ROVER P/N TYK500050, LR0022460
HYUNDAI / KIA SP-IV, SPH-IV, SP-IV RR	MERCEDES BENZ 236.12, 236.14, 236.15, 236.41
HYUNDAI NWS-9638	MINI 83 22 0 142 516, 83 22 2 152 426
JAGUAR FLUID 8432	MITSUBISHI ATF-J2, SP-IV
JASO 1-A-LV	NISSAN MATIC S, MATIC W
JWS 3324	SAAB 93 165 147
	TOYOTA WS
	VOLVO 6 SPEED (P/N 31256774, 31256675)
	VOLKSWAGEN G 052 540, 055 005, G055 162
	ZF 6 SPEED (S671 090 255)

Safety Data Sheet

Safety data sheet can be requested via website www.toyointernational.com or you may also can get them from your local agent / supplier.

SDS Number: LP19-04

Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Suggested temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled.

Stirring is recommended in order to prevent ingredients from separating.

Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 3 years or 36 months

Condition of the product must in the unopened original container

Available Packing Sizes

Bottle	1 liter
Pail	18 liter
Drum	209 liter

Part Number

8696L-0660
8696L-0661
8696L-0662

Packing Type

12 pcs per box

Updated 08.10.2022

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

TOYO-G