



# EAJ 933S Silicone Grease



PROFESSIONAL MAINTENANCE KIT

[www.toyointernational.com](http://www.toyointernational.com)



60g  
24pcs/ box

PART NO :8696G-1291

## PRODUCT DESCRIPTION

EAJ 933S is a non-toxic, non-melting & non-curing silicone grease designed for sealing, lubricating, and waterproofing rubber and plastic parts. The high dielectric strength properties of this product allows it to be used for insulates valves, electrical contacts, spark plugs, battery terminals, and fasteners from moisture, and protects metal parts against corrosion.

## FEATURES AND BENEFITS

- It is resistant to oil, water and chemicals and with a temperature range of -40°C to 224°C
- Safe on most rubber and plastic
- High dielectric strength, ideal for electrical insulating purpose

## PRODUCT APPLICATION

- O-rings, mechanical seal, spark plug, fasteners, plastic gear, battery terminal, electrical contacts, valves, gaskets

## DIRECTION FOR USE

1. Before application, clean the surface to be treated with Toyo Grease® Contact Cleaner spray for sensitive electrical contact. And with Toyo Grease® Brake & Parts cleaner spray for general plastic, rubber and metal surface.
2. Ensure the surface is clean and dry before application.
3. Apply EAJ933S Silicone grease to the parts that require protection.
4. Reassemble parts and wipe off excess material.

## PHYSICAL & CHEMICAL PROPERTIES

NLGI Grade	2
Worked Penetration @ 25°C / 77°F, ASTM D-217	265 - 295
Appearance	Smooth, tacky
Specific gravity	0.98 – 1.03
Colour	Translucent white
Dielectric constant	2.83
Dielectric strength	388
Dropping point, ASTM D-2265	Non-Melt
Temperature range	-40°C to 224°C / -40°F to 435°F

### Safety Data Sheet

Safety data sheet can be requested via website [www.toyointernational.com](http://www.toyointernational.com) or you may also can get them from your local agent/ supplier.  
SDS Number: GP10-01

### Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Keep away from children.

### Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 3 years or 36 months  
Condition of the product must in the unopened original container

### Disclaimer:

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

# TOYO GREASE

Issued: 05 OCT 2020  
TOYO GREASE MANUFACTURING | The Grease & Lubricant Manufacturer  
A Member Of NLGI, USA | National Lubricating Grease Institute